

#### DESCRIPTION

Burnstop IM-Thatch is Flame retardent for the aftercare treatment of straw and reed for new thatched roofs.

Burnstop IM-Thatch grants excellent flame retardent properties to the new roofs on which it is applied.

#### USAGE

Burnstop IM-Thatch is Flame retardent for the aftercare treatment of straw and reed for new thatched roofs.

Burnstop IM-Thatch grants excellent flame retardent properties to the new roofs on which it is applied.

#### PROPERTIES

- Non Toxic
- Ecological

- Colorless after treatment
- Fast penetration/impregnation and dry time
- Not aggressive on wood or on fibres

CHARACTERISTICS
-----------------

Form:	Liquid
Colour:	Light yellow
Odour:	n/a
рН 20°С:	$\pm 6$
Melting point:	n/a
Inflammability:	Not flammable.
Explosion hazard:	Not explosive.
Density at 20°C:	$\pm$ 1,22
Solubilité dans l'eau:	Entièrement miscible

#### PREPARATION

Gently agitate the product for 30 seconds before pouring it into a sprayer. After this operation the product is ready for use. Application in two layers with a low pressure pump is recommended.

#### APPLICATION

- Burnstop IM-Thatch can be applied with a low pressure pump on different straw and reed fibres without specific precautions for people or the environment.
- The new surfaces should be cleaned before applying the product. The Cleaning product has to be completly removed before the application of the Burnstop IM-Thatch
- Don't apply when it rains or freezes
- The temperature of the support should be minimum 5°C



TECHNICAL SPECIFICATIONS According to 1907/2006/CE

Review date 22/07/2013

# CONSUMPTION

- between 3 and 4 m<sup>2</sup> per liter, depending on the porosity of the support.

## RESTRICTIONS

No application in case of rain or frost.

## CLEANING OF EQUIPMENT AND STAINS

Immediately clean with water.

## STORAGE

In a dry, frost free space.

Maximum storage time is 1 year from manufacturing date.

# CONDITIONING

### **IMPORTANT INFORMATION**

#### Safety precautions:

This product is not dangerous. In case of doubt concerning usage and/or application please consult the Material Safety Data Sheet.

The technical information provided in this document is the result of our best experience. The use of this information may not in any way lead to responsibility on our part. Our wish is to provide users of the product described here with several application possibilities. It is up to the user to adapt our information to the specific conditions under which he is operating or to consult us in case of doubt. We can not be held accountable for any failures resulting from applying this product. Please help us help you more effectively; do not hesitate to communicate any improvements to us. Thank you.

