

# TECHNICAL SPECIFICATIONS

According to 1907/2006/CE

Review date 22/07/2013

Page: 1/2

### **DESCRIPTION**

Burnstop IM-WOOD COAT is a transparrant Flame retardent for the aftercare treatment of wood supports and like MDF, multiplex boards, etc.. This product can also be used on parquets and other horizontal supports

Burnstop IM-WOOD COATgrants excellent flame retardent properties to the wood supports on which it is applied.

### **USAGE**

Burnstop IM-WOOD COAT is Flame retardent for the aftercare treatment of wood supports and wood applications, the product has been developed for vertical and horizontal supports. The product can be used on different type of wood supports with porous caracteristics.

### **PROPERTIES**

- Non Toxic - Colorless after treatment

- Ecological - Fast penetration/impregnation and dry time

- Not aggressive on wood or on fibres

### **CHARACTERISTICS**

Form: Liquid Colour: Transparrant

Odour:n/apH 20°C: $\pm$  6Melting point:n/a

**Inflammability:** Not flammable. **Explosion hazard:** Not explosive.

**Density at 20°C:**  $\pm 1,22$ 

Solubilité dans l'eau: Entièrement miscible

### **PREPARATION**

Gently agitate the product for 30 seconds before pouring it into a sprayer. After this operation the product is ready for use. Application in two layers with a low pressure pump is recommended.

### **APPLICATION**

- Burnstop IM-WOOD COAT can be applied with a low pressure pump on different wood supports without specific precautions for people or the environment.
- The surface should be cleaned before applying the product. WOOD COAT
- Don't apply when it rains or freezes
- The temperature of the support should be minimum 5°C



# TECHNICAL SPECIFICATIONS According to 1907/2006/CE

Page: 2/2

Review date 22/07/2013

CC	NSI	TIM	rpi	rt <i>c</i>	M
		. <i>)</i>   <b>V</b>			, ,

- between 3 and 4 m<sup>2</sup> per liter, depending on the porosity of the surface.

### RESTRICTIONS

No application in case of rain or frost.

## **CLEANING OF EQUIPMENT AND STAINS**

Immediately clean with water.

### **STORAGE**

In a dry, frost free space.

Maximum storage time is 1 year from manufacturing date.

### CONDITIONING

### **IMPORTANT INFORMATION**

### **Safety precautions:**

This product is not dangerous. In case of doubt concerning usage and/or application please consult the Material Safety Data Sheet.

The technical information provided in this document is the result of our best experience. The use of this information may not in any way lead to responsibility on our part. Our wish is to provide users of the product described here with several application possibilities. It is up to the user to adapt our information to the specific conditions under which he is operating or to consult us in case of doubt. We can not be held accountable for any failures resulting from applying this product. Please help us help you more effectively; do not hesitate to communicate any improvements to us. Thank you.

